



**DRIVEWAY APPLICATION**

Owner Name: \_\_\_\_\_ Princeville Address: \_\_\_\_\_

Email: \_\_\_\_\_ Cell: \_\_\_\_\_

Contractor: \_\_\_\_\_ Email: \_\_\_\_\_ Cell: \_\_\_\_\_

Architect: \_\_\_\_\_ Email: \_\_\_\_\_ Cell: \_\_\_\_\_

Projected work dates: \_\_\_\_\_

Driveway Color: \_\_\_\_\_ Colorant Type: \_\_\_\_\_

Sheen: \_\_\_\_\_ Stamp Type: \_\_\_\_\_

Required sublayer of: Gravel  Sand  Depth: \_\_\_\_\_”

Lot square footage: \_\_\_\_\_ Existing hardscape sqft: \_\_\_\_\_ Original Hardscape \_\_\_\_\_%

Additional Hardscape sqft: \_\_\_\_\_ New hardscape \_\_\_\_\_%

Please Attach:

- A Copy of property site plan with driveway dimensions, setback lines and drainage swale location (if applicable).
- A photo of the location.
- \$500 Deposit to be held by PHCA for the duration of the project.

Per CDC Rules:

2.14.3 Driveway setbacks: • 3’ side (or adjoining property) lot line setback. • Driveway may flair to within 1’ from the projected side lot line at the roadway starting 10’ from edge of the asphalt. • Standard lot (street frontage one side) wall and fence

6.13 All driveways shall be paved with one or a combination of the following materials: colored concrete, stamped concrete, natural stone pavers, flagstone, wire-cut brick, fired clay pavers or exposed aggregate. Specifications of the proposed materials are to be provided. • Accent strips or complementary materials are highly recommended. • **Driveway approaches shall conform to the existing drainage swale unless other alternatives are approved. If a culvert is used, it shall be appropriately sized, concealed from view, and properly maintained.** • Driveways in excess of 40’ in length shall have a paved space for turnaround of vehicles. • Driveway width shall be: A minimum of 12’. A minimum of 16’ and maximum of 30’ at the street.

**Once complete, call (808) 977-8716 to schedule a Final Inspection.**